

Delta 9000 Series



Delta 9000-C15

Delta 9000-T15

Specification

The Delta 9000 Series of telephones have been designed to work in any heavy duty environment, supplied in a robust aluminium alloy die-cast housing incorporating a spring loaded door (Delta 9000 –T15), it will offer protection against the outdoor environment, vandal resistant and weatherproof.

The Delta 9000-C15 and Delta 9000-T15 meet all the latest European / UK standards for EMC, telephony, waterproofing IP66, and lightning protection together with offering the level of performance and reliability demanded in harsh environments.

DTMF (Dual Tone Multi Frequency)

Standard and SMART Analogue and VoIP-SIP options available

Successfully tested with Direct Exchange Lines (DEL) and most PABX, PBX and PAX systems.

Main Product Features

1. Robust aluminium alloy die-cast housing
2. Full keypad incorporating 10 programmable memories with speed-dial, Illuminated buttons are available as an option
3. Door Cover | Delta 9000-T15: Spring loaded self - closing, convenient for use.
4. Weather resistant to IP67 standard, service temperature range from -30' to +75'C
5. Magnetic reed hook-switch
6. Telephone line powered. No external power or battery back-up required.
7. Lightning protection to ITU-T recommendation K.21
8. Handset: High anti-knock resistance, Weatherproof, armoured cable.
9. Hearing Aid compatible receiver, Noise cancelling microphone.
10. Handset integrity wiring to enable the telephone system to check if the telephone unit is still operational.
11. Vandal resistant and tamper-resistant hardware
12. Easy installation / replacement