

## tiptel 1010

### Analogue system telephone with remote programming

While installing several analogue telephones which support standard functions used in hotels or nursing homes the programming effort for every single telephone was enormous. Reception, wake-up call, room service, request for help etc. always had to be programmed to the same function keys of every single telephone.

But, this is a thing of the past! With the tiptel 1010 you only need to programme one telephone which will then be defined as "master". Than every further connected telephone receives it's programming via a phone call. Now, the master telephone has been cloned. And the telephones are ready to use!

Also the programming lock against accidental changes will be directly cloned. Furthermore it is possible to equip the big labelling area with individually designed or already printed paper inlays.

This development safes a lot of time and costs. What an advantage when installing big telephone systems.

#### Highlights

##### tiptel 1010

- Remote programming and cloning function
- Clearly visible LED as Message Waiting Indicator (MWI)
- Hands-free (half-duplex), open listening
- Hearing aid compatible (integrated magnetic field generator)
- Connection possibility for a corded headset
- 16 different ring tones
- Line fed (no external power supply or batteries needed)
- Adjustable tilting angel
- Wall-mountable



# tiptel 1010

## Analogue system telephone with remote programming



### Telephone functions

- Hands-free (half-duplex), open listening, signalled by the integrated LED
- Adjustable loudspeaker and ringing volume
- Mute key with LED
- Dialling preparation
- 16 different ring tones
- 10 one touch memory keys with caller ID (one touch memory key flashes with incoming call from programmed number)
- Clearly visible LED as Message Waiting Indicator (MWI)
- Headset jack
- Suitable for PBXs
- Hearing aid compatible (integrated magnetic field generator)
- Adjustable tilting angel in three steps
- Stand is useable as wall holder

### Technical specifications

- Dual-CLIP: FSK/DTMF
- Dial mode: touch tone (DTMF)
- Flash key, switchable (100ms/240ms)
- Message Waiting Indicator\*: FSK, polarity reversal, increased voltage, special call signal
- Line feed (no external power supply or batteries needed)
- For analogue connection according to ETSI ES 203021

### Additional information for system installers

- Lock setting (special function for hotels)
- Security code
- Special CLIP settings for telephone systems
- Health care application (automatic pick-up)\*
- Duplication of telephone settings (device cloning)

\* This service has to be supported or activated by the network provider or telephone system

### Model

tiptel 1010

### Article-No.

1081500

Subject to changes | 11/2012